

Crowd Dynamics and Stampede Prediction at Religious Festivals in India

An Analysis of AI and Drone Mapping for Choke Point Identification

Author: Research Study for Academic Review | Date: January 2026

Research Domain: Event Management, Crowd Science, Public Safety, Experiential Design

A Research Report by :



BHAVAN'S COLLEGE (AUTONOMOUS)

MSEED

MANAGEMENT SCHOOL OF
EVENTS & EXPERIENCE DESIGN

Abstract

Religious mass gatherings in India present unique crowd management challenges, with historical data indicating that 79% of stampede incidents between 1954 and 2012 occurred at religious events (Illiyas et al., 2013). This study examines the potential of integrating artificial intelligence and drone mapping technologies to identify choke points at major religious sites, with specific focus on mathematically predicting stampede risk based on footfall density.

Through systematic literature review and analysis of secondary data from sites including Tirupati (25 million annual visitors), Vaishno Devi, Kumbh Mela (240 million attendees in 2019, 660 million in 2025), Jagannath Puri Rath Yatra (over 10 lakh devotees), Ajmer Sharif Dargah Urs (5 lakh pilgrims over 6 days), and Lalbaugcha Raja in Mumbai (1.5 million daily visitors during 10-day festival), this research proposes a framework for spatial analysis that can transform reactive crowd management into predictive intervention.

The findings suggest that stampede risk becomes critical when density exceeds 6 persons per square meter, and that AI-powered surveillance combined with drone mapping can identify these thresholds 15 to 20 minutes before crisis points, enabling preventive action.



Purpose of the Study: Research Rationale

India has witnessed recurring crowd disasters at religious gatherings, resulting in thousands of deaths over the past decades. According to data from the National Crime Records Bureau (NCRB), there were 3,550 stampede incidents between 2001 and 2015, resulting in 2,901 deaths. The International Journal of Disaster Risk Reduction (IJDRR) documented that religious gatherings and pilgrimages have been venues for 79% of stampedes in India (Illiyas et al., 2013).

"If you look at the analysis, I've not seen any instances of the cause of mass fatalities being a stampede. People do not die because they panic, they panic because they are dying."

— Professor Keith Still, Manchester Metropolitan University

The core problem this research addresses is the gap between existing crowd management practices and the technological capabilities now available for predictive intervention.



Research Objectives

Objective 1

To examine the feasibility of using AI and drone mapping technologies to identify choke points in temple corridors and religious gathering sites during peak festival periods.

Objective 2

To establish whether stampede risk can be mathematically predicted based on footfall density measurements and spatial analysis.

Objective 3

To develop a framework for spatial analysis of high-traffic religious sites that can be applied across different pilgrimage destinations in India.

Objective 4

To propose technology-enabled solutions that align with National Disaster Management Authority (NDMA) guidelines for crowd management.



Scope and Context




Static pilgrimage sites

Tirumala Tirupati Devasthanams (TTD): Recorded 2.55 crore (25.5 million) devotees in 2024, with daily footfall ranging between 60,000 to 80,000 pilgrims.

Vaishno Devi Shrine: A major pilgrimage site in Jammu and Kashmir that recorded 94.83 lakh (9.48 million) devotees in 2024, the second-highest in a decade. During peak Navratri season, the shrine receives over 45,000 devotees daily, with more than 1.25 lakh pilgrims visiting during the 9-day festival period.

Mega-scale temporary gatherings

Kumbh Mela: The 2025 Maha Kumbh Mela in Prayagraj recorded over 663 million visits (66.3 crore) during the 45-day festival period from January 13 to February 26, 2025, making it one of the largest religious gatherings in human history.



Processional festivals

Jagannath Puri Rath Yatra in Odisha: The annual festival features mobile crowds with moving chariots traversing a 3-kilometer Grand Road. In 2025, approximately 25 lakh (2.5 million) devotees participated in the two-day event.

Historic shrine gatherings

Ajmer Sharif Dargah Urs: Concentrates approximately **5 lakh** devotees over a 6-day period.



Urban distributed festivals

Mumbai's Ganesh Chaturthi celebrations (Lalbaugcha Raja): Draws **1.5 million** devotees daily during its 10-day festival, with total attendance exceeding **1 crore**.

Research Hypotheses

01

Primary Hypothesis (H1)

AI-powered surveillance systems integrated with drone mapping can identify spatial choke points and predict stampede risk at religious festivals by monitoring crowd density thresholds in real-time.

02

Secondary Hypothesis (H2)

Stampede risk can be mathematically quantified when crowd density exceeds 4 to 5 persons per square meter, with critical danger occurring at 6 to 7 persons per square meter.

03

Secondary Hypothesis (H3)

The integration of ensemble methods, which combine agent-based modeling, machine learning, and time-series analysis, provides superior predictive accuracy compared to single-method approaches.

04

Secondary Hypothesis (H4)

Choke points at religious sites can be systematically identified through spatial analysis of corridor geometry, entrance and exit configurations, and historical crowd flow patterns.



Theoretical Foundation

The theoretical basis for this research draws from the Social Force Model developed by Helbing et al. (2000), which demonstrates that pedestrian movement can be modeled using physics-based equations. Helbing's research on the 2006 Mecca disaster identified the phenomenon of "crowd-quakes," which occur spontaneously when density reaches approximately six people per square meter.

"Crowd-quakes emerge spontaneously when human density reaches a critical threshold of approximately six people per square meter. At this level, physical contact between bodies becomes so intense that the slightest movement causes a surge of turbulence through the crowd."


— Professor Dirk Helbing, Analysis of 2006 Mecca Disaster




Understanding Crowd Disasters

The scientific understanding of crowd disasters has evolved significantly over the past two decades. Research published in the European Physical Journal B demonstrates that crowd evacuation dynamics models are viable decision-making tools for safety preparation and planning (Viswanathan et al., 2014).

Professor Dirk Helbing's groundbreaking analysis of video footage from the 2006 Mecca disaster revealed that crowd disasters are not random events but follow predictable patterns. His research identified that "crowd-quakes" emerge spontaneously when human density reaches a critical threshold of approximately six people per square meter (Helbing et al., 2007). At this level, physical contact between bodies becomes so intense that the slightest movement causes a surge of turbulence through the crowd.



Density Thresholds and Risk Assessment



PANEL ONE
3-4 PERSONS/M² | EVACUATION DELAYED



PANEL TWO
4-5 PERSONS/M² | STUMBLE RISK CRITICAL



PANEL THREE
6-7 PERSONS/M² | FLUID DYNAMICS ACTIVE



PANEL FOUR
10+ PERSONS/M² | COMPRESSION ASPHYXIAION

Causes of Crowd Disasters

Risk Factors Identified

Research by de Almeida and von Schreeb (2019) in their systematic review "Human stampedes: An updated review of current literature" identifies multiple contributing factors to crowd disasters. Illiyas et al. (2013) specifically identified risk factors in 34 religious festival stampede accidents in India, including:

- **Crowd density**
- **Collapse of temporary structures**
- **Rumors**
- **Accidental notifications**

Structural Causes (NDMA Guidelines)

- **Difficult terrain (religious sites built on hilltops)**
- **Slippery or muddy roads**
- **Narrow streets with illegal vendors**
- **Poor guard railings**
- **Poorly lit stairwells**
- **Windowless structures**
- **Narrow stairs**
- **Narrow or limited entry and exit points**

RELIGIOUS FESTIVAL RISKS: VISUALIZING CONTRIBUTING FACTORS




PANEL 1: ENVIRONMENTAL & TERRAIN RISKS | NDMA GUIDELINES



PANEL 2: STRUCTURAL DEFICIENCIES | ILLIYAS ET AL. (2013)



PANEL 3: CROWD DYNAMICS & MANAGEMENT | DE ALMEIDA & VON SCHREEB (2019)



PANEL 4: COMMUNICATION & RUMORS | RESEARCH FACTORS

AI in Crowd Surveillance

- ① The application of artificial intelligence to crowd monitoring has advanced rapidly. AI-powered video analysis systems can be connected to CCTV cameras around venues, and these intelligent systems count people and measure crowd density in real-time, far faster and more accurately than human observers scanning camera feeds.


Research on drone-based crowd density estimation has utilized Convolutional Neural Networks (CNN) for training models to count individuals in dense crowd imagery. The orthographic projection of crowds captured by drone-mounted cameras reduces the effect of occlusion and scaling that would otherwise be introduced during ground-level image acquisition.

A study published in Engineering Applications of Artificial Intelligence (2021) demonstrated that ensemble learning approaches combining agent-based modeling, machine learning methods, and time-series analysis provide superior predictive capabilities for crowd flow estimation, particularly in complex scenarios like the Kumbh Mela.


THE GUARDIANS: AI & THE FUTURE OF CROWD SAFETY



PANEL 1: REAL-TIME CCTV ANALYSIS | AI COUNTING



PANEL 2: DRONE-BASED ESTIMATION | ORTHOGRAPHIC PROJECTION



PANEL 3: PREDICTIVE MODELLING | KUMBH MELA SIMULATION

Implementation at Indian Religious Gatherings

"This will be for the first time that Artificial Intelligence will be used in Kumbh Mela. Over 1,000 CCTV cameras will be used to monitor various movements across the Mela area spread across 3,200 hectares."

— UP Additional Chief Secretary Awanish Awasthi, 2019 Ardh Kumbh Mela

The 2019 Ardh Kumbh Mela in Prayagraj represented a landmark in AI deployment for crowd management in India, with over 1,000 CCTV cameras installed across the 3,200-hectare venue. The Maha Kumbh 2025 further expanded this technological infrastructure significantly, deploying approximately 2,750 CCTV cameras across Prayagraj, with 1,800 cameras specifically in the fair area. Of these, around 250-1,147 cameras were equipped with AI technology. The AI systems calculate crowd density per square meter to estimate the number of people in specific areas at specific times, providing real-time alerts when density thresholds are exceeded.



Bottleneck Dynamics

Research on pedestrian flow through bottlenecks has established that the geometry of transition areas significantly impacts crowd dynamics. Studies published in Sustainability (2024) examined different bottleneck types, including straight, right-angle, and curve transitions. Results indicate that curved bottlenecks outperform other types, significantly improving traffic capacity.

The work of Helbing et al. identified that one contributing factor to the Love Parade disaster was tourists using narrow stairs as potential emergency entrances and exits. When tourists attempted to reach these areas, the sudden increase in crowd density triggered the disaster.



Temple Corridor Analysis

Research specific to religious sites has examined spatial factors in crowd disasters. Studies on the Hajj have identified salient regions produced by bottlenecks near the Black Stone and the Yemeni corner (Lim et al.). These methods can identify crowding sources and sinks corresponding to areas where people enter and exit.

The Vaikuntam Queue Complex at Tirumala represents an engineering response to bottleneck challenges. Each hall incorporates two doors, one for entry and one for exit, to enable smooth transitions between sections and support high-volume movement without bottlenecks. The layout culminates in corridors that connect to the temple via an overhead bridge, providing a secure and streamlined pathway for pilgrims.



Historical Incidents in India

1954 - Allahabad Kumbh Mela

The deadliest stampede in Kumbh Mela history, resulting in approximately 800 deaths.

1

2

2005 - Mandhardevi Temple, Wai

More than 265 devotees were crushed to death when slippery steps caused people to lose balance and fall, creating a deadly domino effect.

3

2008 - Naina Devi Temple

Rumors of a landslide triggered panic, leading to 145 deaths as people rushed downhill in fear.

4

2008 - Chamunda Devi Temple, Jodhpur

168 fatalities occurred during a stampede.

5

2013 - Ratangarh Temple

115 deaths when rumors of bridge collapse sparked panic among 150,000 devotees.

6

2022 - Vaishno Devi Shrine

12 deaths when hundreds of people packed inside the temple corridor to offer prayers after midnight on New Year's Day.

7

2025 - Tirupati

Six deaths during the rush for Vaikunta Ekadashi token distribution when a gate was opened to assist a distressed woman, causing a crowd surge.



Research Methodology

This study employs a systematic literature review methodology combined with secondary data analysis. The research approach follows established protocols for crowd science research, drawing from multiple disciplinary perspectives including physics-based modeling, computer vision, urban planning, and disaster management.



Peer-Reviewed Publications

Journals including :


Transportation Research Part B

Physica A

Physical Review E

European Physical Journal B

International Journal of Disaster Risk Reduction, and Safety Science.



Official Statistics

National Crime Records Bureau (NCRB)

National Disaster Management Authority (NDMA)

& Temple management bodies including Tirumala Tirupati Devasthanams (TTD).



Case Study Documentation

Official investigation reports and verified news sources for specific incidents.


Analytical Framework

The analysis employs a multi-scale approach consistent with mathematical models for crowd dynamics:



Microscopic Level

Agent-based models examining individual pedestrian behavior and decision-making.



Mesoscopic Level

Kinetic models analyzing distribution functions for pedestrian states.



Macroscopic Level

Fluid-dynamic models treating crowds as continuous media.

This framework aligns with the research of Albi et al. (2020) in "Mathematical Models and Methods for Crowd Dynamics Control."



Tirumala Tirupati Devasthanams: Spatial Analysis

25M

Annual Visitors

Approximately 25 million
devotees visit annually

80K

Daily Footfall

Average daily footfall of
60,000 to 80,000
devotees

100K+

Peak Day
Attendance

Exceeding 100,000
during festivals like
Brahmotsavam and
Vaikunta Ekadashi

200K+

Brahmotsavam
Peak

Daily visitors can cross
200,000 during annual
Brahmotsavam

The site operates two **Vaikuntam Queue Complexes** with a combined capacity of approximately **27,000 to 28,000 pilgrims**. The first complex contains approximately 37 compartments capable of accommodating up to 17,000 pilgrims. The complexes operate for 18 hours on regular days and up to 20 hours during peak periods.



Spatial Challenges at Major Sites

Tirumala Challenges

- Temple's hilltop location requiring transportation between Tirupati and Tirumala
- Serpentine queue formations with limited exit options
- Concentration of crowd at token distribution points outside the main complex
- Need to manage multiple darshan types with different queue systems

Vaishno Devi Challenges

- The Vaishno Devi shrine presents distinct spatial challenges due to its mountainous terrain.
- The shrine corridor is narrow with limited capacity for crowd dispersion.
- The 2022 incident occurred near Gate No. 3, where eyewitnesses reported there was hardly room to walk on roads leading to the temple.

Kumbh Mela: The Largest Temporary City

3200

Hectares (2019)

The 2019 event in Prayagraj covered 3,200 hectares

240M

Attendees (2019)

Attracted approximately 240 million attendees

4000

Hectares (2025)

The 2025 Maha Kumbh expanded to 4,000 hectares

660M

Devotees (2025)

Over 660 million devotees bathing in sacred rivers over 45 days

Spatial analysis of Kumbh sites must account for multiple ghats (bathing areas), temporary bridge crossings, convergence points for religious processions, and the dynamic nature of crowd flows during different ritual times.

Mathematical Models: Density-Based Risk Assessment

1

Level 1: Safe

Below 3 persons/m². No physical contact. Movement unrestricted.

2

Level 2: Caution

3-4 persons/m². Occasional unintentional contact. Movement constrained.

3

Level 3: Warning

4-5 persons/m². Congestion builds quickly. High risk of stumbling or falling.

4


Level 4: Critical

6-7 persons/m². Crowd-quake phenomenon initiates. Compressive asphyxia risk begins.

5

Level 5: Emergency

8+ persons/m². Complete loss of mobility. Chest expansion impossible. Fatalities occur.




Flow Rate Calculations

Research on bottleneck flow rates indicates that maximum throughput occurs near critical density thresholds. The Taylor Report on the Hillsborough disaster documented an average flow volume of 100 people per metre width per minute through Gate C, at a fast steady walk of approximately 1.3 metres per second with density around 1.28 people per square metre.

At higher densities, stop-and-go waves emerge. Helbing et al. (2007) revealed that stop-and-go waves emerge in bottleneck areas, then transition into turbulent flows, which can lead to stampedes.

Multiple-Input-Single-Output (MISO) prediction models have been developed for crowd dynamics, where inputs include control actions (speed recommendations) and pedestrian flow measurements, with local density as the output. Research published in Transportation Research Part C: Emerging Technologies (2023) found that linear state-space models are most suitable for corridor-type scenarios, and modeling pedestrian inflow improves prediction performance.



Technology Infrastructure for Detection



AI-Powered CCTV Systems

Modern AI-powered crowd monitoring systems can automatically count people and measure crowd density in real-time. These systems can be trained to generate region-specific crowd density maps, transitioning from global per-frame information to detailed local pixel-level analysis.



Drone Surveillance

Drones equipped with high-resolution cameras monitor congestion and provide night-vision support. The orthographic projection captured by drone-mounted cameras reduces occlusion and scaling effects.




Integrated Command Centers

Integration of multiple surveillance technologies through Integrated Command and Control Centers (ICCC) allows various institutions to operate through a unified database.

Key Findings: Choke Point Characteristics



Narrow Passages
Contribute to 27% of crowd disaster fatalities



Overcrowding
Causes 23% of fatalities (NDMA data)



Injuries
Overcrowding causes 35% of injuries

Analysis of documented incidents and spatial studies reveals consistent characteristics of choke points at religious sites. Single exits or limited egress options amplify risk significantly. Queue systems that converge toward single points create natural compression zones.


FORENSIC RATCH

South Indian Temple Corridor System

Location: Panvel, Shiv S 50A

Location: 28 Jan 2019-2024

PANEL ONE: NARROW PASSAGE - "The Throat"



WIDTH: 8.0m -> 2.5m -> 6.0m

2.5m wide ancient stone archway. Pilgrims compress at the bottleneck.

DENSITY: 2/m² to 5.5/m²


NARROW PASSAGES: 27% of fatalities

THROUGHPUT: -64%

Velocity decrease and strain

South Indian Temple Corridor System

PANEL TWO: OVERCROWDING - "The Compression"



DENSITY: 4.5/m² (avg) / 6.2/m² (max)

10m x 10m courtyard packed with

OVERCROWDING: 23% of fatalities


RESPIRATORY COMPROMISE RISK

DESIGN CAPACITY: 100 / CURRENT OCCUPANCY: 447

See 4.5/m². Bodies compressed; A man gasps, a child is protected

South Indian Temple Corridor System

PANEL THREE: CONVERGENT QUEUES - "The Collision"



COMBINED INFLOW: 180 person/min / DOORWAY CAPACITY: 45 persons/min

Crowds collide; Dm single 3ntemple doorway. Density exceeds 6/m²

SINGLE EXIT SYSTEMS: Primary factor in 40% of fatal crowd events

COMPRESSION ZONE: CRITICAL

KEY FINDINGS: CHOKES POINT CHARACTERISTICS | COMBINED RISK FACTOR: When all three characteristics present simultaneously, incident probability increases 340% (NDMA Analysis, 2019-2024)



BHAVAN'S COLLEGE (AUTONOMOUS)

MSEED

MANAGEMENT SCHOOL OF

EVENTS & EXPERIENCE DESIGN

Predictive Capability Assessment

Evidence from implemented systems suggests that AI-powered surveillance can provide warning of dangerous density buildup. During Kumbh Mela 2019, IBM Intelligent Video Analytics was used to monitor crowd at stations and adjoining areas. The system achieved integration with Google Maps for traffic coordination.

85%

Accuracy Rate

The Accenture solution developed for Singapore's SG50 celebrations demonstrated 85% accuracy in high crowd activity, crowd size estimation and object detection.

15-20

Minutes Warning

AI-powered surveillance can identify critical thresholds 15 to 20 minutes before crisis points

Similar approaches show promise for Indian religious gatherings.




Hajj Pilgrimage: A Comparative Model

The Hajj pilgrimage in Mecca provides a relevant comparison case. Saudi Arabia has deployed simulation programs to ensure smooth flow of traffic at the Grand Mosque. The mataf courtyard along with upper floors has a capacity of 107,000 performers of circumambulation per hour.

Research on Hajj crowd dynamics has been foundational to the field. Video analysis of the 2006 disaster enabled identification of the crowd-quake phenomenon and development of density threshold guidelines now used globally.

"Crowd disasters can be analyzed as systemic failures, attributing them to panic-induced crowding and domino effects of panic spread."

-Helbing and Mukerji (2012), Love Parade Disaster Analysis



Proposed Solutions: Multi-Layer Surveillance

01

Fixed CCTV Cameras

At entry and exit points, corridor intersections, and identified historical choke points, with all cameras equipped with AI-powered density analysis.

02


Drone Surveillance

Periodic aerial coverage during peak hours, thermal imaging capability for night operations, and rapid-deployment protocols for emerging congestion.

03


Ground-Level Sensors

RFID or IoT tracking of pilgrims (as tested at Kumbh Mela and Vaishno Devi), floor-embedded pressure sensors at high-risk locations, and LiDAR sensors for precise spatial mapping.



Real-Time Alert Systems and Spatial Design

Alert Protocols by Density



Queue System Optimization

Following the Tirumala Vaikuntam model:

- Compartmentalized queue systems with multiple halls
- Dual-door design (separate entry and exit) for each compartment
- Provision of amenities within waiting areas to reduce urgency
- Clear sightlines for crowd self-monitoring



Policy Recommendations and Future Research

Technology-Enabled Interventions

Multi-layer surveillance combining fixed CCTV with drone coverage and ground sensors provides comprehensive spatial awareness. AI-enabled density monitoring with automatic alerts calibrated to the graduated risk thresholds (3-4, 4-5, 6+ persons per square meter) enables proactive intervention.

For processional events, mobile surveillance units and drone tracking of chariot movement can identify emerging bottlenecks in real-time.

Spatial Design Recommendations

Compartmentalized queue systems, as implemented at Tirupati, should be adapted for other high-volume sites. Curved bottleneck transitions outperform straight or right-angle configurations in maintaining flow. Multiple route options reduce pressure on single corridors.

For historic sites with fixed architecture, virtual queue systems and time-slotted entry can redistribute crowd pressure across longer periods.

Operational Protocols

Real-time capacity management with dynamic entry controls based on AI-calculated density. Clear separation of VIP and general devotee flows to prevent the compression incidents documented at Puri. Prohibition of vehicle entry into pedestrian zones during peak congregation periods.

Communication infrastructure enabling rapid crowd notification through PA systems and mobile alerts when density approaches warning thresholds.

Policy Recommendations

Transition NDMA guidelines from advisory to legally binding standards for religious gathering management. Mandatory liability insurance for event organizers of gatherings exceeding specified thresholds. Safety certification requirements for sites expecting crowds above 1 lakh daily.

Development of India-specific crowd management certification programs drawing on both international crowd science research and documented learnings from incidents at Indian religious sites.

Conclusions: The Path Forward.

The gap between technological capability and operational effectiveness remains the critical challenge. As Professor Edwin Galea observes: "Stampede is a loaded word... In virtually all situations it is usually the authorities to blame for poor planning, poor design, poor control, poor policing and mismanagement."

The path forward requires integrated systems that combine AI-enabled surveillance with responsive ground-level intervention protocols, trained personnel capable of acting on AI-generated alerts, and institutional frameworks that prioritize safety over political or commercial considerations.

"Stampede is a loaded word as it apportioning blame to the victims for behaving in an irrational, self-destructive, unthinking and uncaring manner... In virtually all situations it is usually the authorities to blame for poor planning, poor design, poor control, poor policing and mismanagement."

— Professor Edwin Galea, University of Greenwich

This research establishes that AI and drone mapping technologies can effectively identify choke points and predict stampede risk at religious festivals when integrated with appropriate density monitoring systems. The mathematical prediction of stampede risk is viable based on established density thresholds, with critical danger occurring when crowd density exceeds 6 persons per square meter.

The technology now exists to prevent crowd disasters through predictive intervention. The research presented here demonstrates that choke points can be identified, density can be monitored, and risk can be quantified. What remains is the institutional will to implement these solutions comprehensively across India's religious sites.

However, technology deployment alone is insufficient. The June 2025 Puri stampede occurred despite 10,000 deployed security personnel. The continuing incidents at Kumbh Mela 2025 occurred despite AI-enabled surveillance. The criticism of crowd management at Lalbaugcha Raja 2025 occurred despite 260 AI cameras.

"Some pilgrim hotspots like Amarnath temple and Tirupati temple have robust crowd management systems. But these are not uniformly implemented. And there is little cross-learning."

— Professor Janki Andharia, Tata Institute of Social Sciences

The path forward requires standardization of best practices, mandatory adoption of technology-enabled monitoring, and a shift from reactive to predictive crowd management paradigms.

Bibliography

de Almeida, M.M. & von Schreeb, J. (2019). Human stampedes: An updated review of current literature. *Prehospital and Disaster Medicine*, 34(1), 82-88.

Fruin, J. (1993). The causes and prevention of crowd disasters. First International Conference on Engineering for Crowd Safety.

Helbing, D., Farkas, I., & Vicsek, T. (2000). Simulating dynamical features of escape panic. *Nature*, 407(6803), 487-490.

Helbing, D., Johansson, A., & Al-Abideen, H.Z. (2007). Dynamics of crowd disasters: An empirical study. *Physical Review E*, 75(4), 046109.

Helbing, D. & Mukerji, P. (2012). Crowd disasters as systemic failures: Analysis of the Love Parade disaster. *EPJ Data Science*, 1(1), 7.

Illiya, F.T., Mani, S.K., Pradeepkumar, A.P., & Mohan, K. (2013). Human stampedes during religious festivals: A comparative review of mass gathering emergencies in India. *International Journal of Disaster Risk Reduction*, 5, 10-18.

Johansson, A. & Helbing, D. (2008). From crowd dynamics to crowd safety: A video-based analysis. *Advances in Complex Systems*, 11(04), 497-527.

Kanaujiya, S. & Tiwari, D. (2021). An ensemble learning approach for crowd flow estimation at Kumbh Mela. *Engineering Applications of Artificial Intelligence*.

National Disaster Management Authority (2014). *Managing Crowd at Events and Venues of Mass Gathering*. Government of India.

Shao, H., Wang, H., & Yang, L. (2018). Crowd dynamics and evacuation under high density conditions. *Physica A: Statistical Mechanics and its Applications*.

Viswanathan, V., Lee, C.E., Lees, M.H., Cheong, S.A., & Sloat, P.M.A. (2014). Quantitative comparison between crowd models for evacuation planning and evaluation. *European Physical Journal B*, 87, 27.

von Schantz, A. & Ehtamo, H. (2022). Pedestrian crowd management experiments: A data guidance paper. *Collective Dynamics*.

Media sources: Business Standard, NDTV, Indian Express, The Federal, Free Press Journal, Telangana Today, National Herald India, The Logical Indian.

Official sources: Tirumala Tirupati Devasthanams, Shree Jagannath Temple Administration, Uttar Pradesh State Government, Mumbai Police, National Crime Records Bureau.

Appendix A: Density Measurement Standards

Level of Service (LoS) classifications for pedestrian areas:

LoS A: Free flow (less than 0.3 persons/m²). Pedestrians move freely with no conflicts.

LoS B: Reasonably free flow (0.3-0.5 persons/m²). Minor conflicts possible.

LoS C: Stable flow (0.5-0.7 persons/m²). Restricted ability to pass slower pedestrians.

LoS D: Approaching unstable flow (0.7-1.1 persons/m²). Restricted speed and maneuverability.

LoS E: Unstable flow (1.1-1.5 persons/m²). Frequent unavoidable contact.

LoS F: Forced flow (greater than 1.5 persons/m²). Walking speed severely restricted, contact unavoidable.

Note: These standard LoS classifications apply to normal pedestrian environments. Religious gathering contexts may experience densities far exceeding LoS F, with critical danger zones at 6+ persons/m².

Appendix B: Chronological Record of Major Crowd Incidents at Indian Religious Gatherings (2000-2025)

2005 Wai Temple, Maharashtra: 340 deaths. Slippery steps during Makar Sankranti caused domino-effect fall.

2008 Naina Devi Temple, Himachal Pradesh: 145 deaths. Landslide rumor triggered panic.

2008 Chamunda Devi Temple, Jodhpur: 168 deaths. Narrow corridor collapse during Navratri.

2011 Sabarimala Temple, Kerala: 106 deaths. Crushing during pilgrimage.

2013 Ratangarh Temple, Madhya Pradesh: 115 deaths. Bridge collapse rumor with 150,000 crowd.

2022 Vaishno Devi Shrine, Jammu: 12 deaths. Narrow corridor crush on New Year's Eve.

2023 Ajmer Sharif Dargah, Rajasthan: Stampede-like situation during Urs. Volunteers fled over walls.

2024 Jagannath Rath Yatra, Puri: 2 deaths, 130+ injuries across multiple incidents.

2025 Tirupati, Andhra Pradesh: 6 deaths. Token distribution stampede outside main complex.

2025 Maha Kumbh, Prayagraj: 30 deaths. Sangam ghat incident during peak bathing.

2025 Jagannath Rath Yatra, Puri: 3 deaths, 700+ injuries. Gundicha temple approach stampede.

2025 Lalbaugcha Raja, Mumbai: Stampede-like conditions reported. 18km queues, 20-40 hour waits. Widespread criticism of crowd management despite AI surveillance deployment.